ALANT®



500 Series





Ideal operator position

 Positioned in the front part of the machine, the operator's seat is as close to the attachment as it can safely be – this gives unrestricted view of the attachment working

• Top class working efficiency - safely

Telescopic handler type off center loader boom

- Excellent, unrestricted field of vision to the work and attachment
- More precision, working efficiency and safety
- The loader boom reaches out not the driver

Well thought-out AVANT ergonomics

- Ample space even for larger operators
- Easily operated, well-positioned controls
- Excellent feel on both drive and hydraulics controls
- Safe and easy access to driver's seat
- ROPS safety frame with tinted plexiglass canopy is standard feature

Four different cab options available

- Certified ROPS safety frame with tinted plexiglass canopy as standard
- AVANT Cab L: consists of windscreen (equipped with wiper), right side window and rear window.
- AVANT Cab LX: has all the features of cab L and, in addition, is equipped with a door and a heater
- AVANT Cab DLX: independent ROPS/FOPS cab that mounts on the machine. It is equipped with a
 heater, noise isolating interior and fabric seat, radio and cab air filter.







Exactly the right size

- Strong enough can handle round bales and big bags
- Compact enough can work in tight situations

Advanced technology

- Stepless hydrostatic transmission
- Hydraulically pilot operated variable displacement drive pump
 driving is smooth, no wearparts in the drive system

Comprehensive options range

- Telescopic loader boom gives more lift height and outreach
- Boom self levelling makes load handling quicker and more precise
- Hydraulic rear lift, boom float, extra work lights, cab etc.



Multi connector system as standard equipment

The multi connector system is standard equipment on Avant 500 series machines and its attachments. It facilitates connecting and disconnecting of attachment hoses considerably, compared with conventional type quick couplings.

Multi connector benefits

- Connects all hoses effortlessly with a single hand movement.
- Releases pressure automatically and is always easy and light to connect.
- No oil drops during connecting or detaching.
- It is not possible to connect the multi connectorin a wrong way.

Safety

Rigid articulation joint

The rigid articulation joint which doesn't swing sideways is a very important feature in a machine of this size. Thanks to this rigid design the risk of tipping over of the machine is essentially smaller, because the rigid articulation joint will not allow excessive sideways movements and the whole weight of the machine acts as counterweight and keeps the chassis stable.

Safety frame

The ROPS safety frame - a standard feature like the tinted plexiglass canopy - is a four post structure which really protects the operator, for instance when driving backward and accidentally hitting an obstacle. The ROPS frame and the optional FOPS canopy are tested and certified and comply with the relevant ISO standards.

Telescopic boom

The telescopic loader boom is an essential part of the great stability. The boom design allows you to keep the boom retracted and the load as close to the machine as possible, simply to be extended only when required.

Load sensor

The load sensor comes as standard in the AVANT 500 series. Audible warning signals are heard if the rear wheels are about to lift off of the ground, warning the operator immediately should he, for example, inadvertently move the load away from the machine with the telescopic boom.

Indoor jobs

Avant 525 LPG

Avant 500 series is now available also with an LPG engine. Avant 525LPG is equipped with a Kubota 23 hp LPG (liquefied petroleum gas) engine. Avant 525LPG is ideal for indoor jobs where a compact yet powerful machine is required and where use of diesel or petrol engines is not possible.

Avant 525LPG compared to diesel models:

- Only CO₂ emissions, no small particles
- Quieter engine





In farming, AVANT has both skill and power







New AVANT 500 Series – the efficient farming machine

Moden farming requires more and more versatility from the machines, and this has been taken into consideration in the design of the new AVANT 500 series. The first requirement is size: the machine must be compact enough to work in tight situations, go through narrow doorways etc. On the other hand it must be strong enough to handle heavier loads. AVANT 500 Series meets these requirements.

Satisified users

User satisfacion is very high among AVANT customers. On thousands of farms around Europe AVANT has proven its capabilities and is today one of the most important machines, making many jobs easier. And the AVANTs are working hard every day. On many farms, AVANT collects more working hours than a tractor.



AVANT 500 – more versatile than ever

The power and capabilities of the new AVANT 500 series is sufficient for most of the jobs on the farm:

- Silage distribution
- Handling of wrapped round bales without damaging the plastic wrapping
- Filling of mixer feeder wagon
- Handling of big bags
- Moving of fertilizer pallets
- Demanuring
- Cleaning and sweeping jobs
- Loading on big and high trailers
- Estate management
- Construction





AVANT – the horse stable tractor







The all round machine for horse stables

AVANT has for many years had a close cooperation with horse stables and horse breeding farms. This long experience is clearly visible both in AVANT loaders and in attachments.

The new AVANT 500 series is exactly the right size multi purpose machine for horse stables.

- Learning to operate the AVANT is very quick and easy – new staff will quickly learn how to drive the machine.
- AVANT 500 can easily handle the bales with a bale grabber, without damaging the plastic wrapping.
- AVANT with an auger is the ideal solution for making fences.
- AVANT and the new horse arena harrow will keep your arena in top shape.
- AVANT is the indispensable tool for demanuring
- In winter you can do the snow removal, sand and salt spreading and other winter maintenance jobs with AVANT
- In summer, AVANT is the machine for lawn mowing, street cleaning and other similar tasks

Landscaping



AVANT – the efficient machine for landscaping

AVANT 500 series, like its big brother 600, really can handle landscaping jobs. This is the work they are doing in over 30 countries already.

AVANT has developed a very comprehensive range of attachments to meet the many varied requirements of landscaping and groundscare. Thanks to the AVANT collection of attachments, one AVANT can undertake the jobs of several different machines. From earthmoving and moving of materials, loading and unloading, digging, leveling, milling and even paving – and also the maintenace jobs like lawn mowing, sweeping etc.

The articulated design and compact dimensions of AVANT 500 mean it can work on any site, and it is easy to transport on a trailer from one work site to another. This means projects are completed more quickly, quality is better and time and money is saved.





AVANT for property maintenance







Property maintenance all-year-round

AVANT 500 series is an efficient machine for property maintenance, also in tight situations. Thanks to the complete, high quality attachment range it tackles the maintenance jobs all-year-round.


In winter, snow removal can be done not only with a bucket but also with a dozer blade, snow plow, snow broom or even snow blower. Sand spreading with the hydraulic or towable spreader is fast, and it can also be done at the same time as snow removal: with the bucket or dozer blade in the front and the spreader in the rear.

The optional spacious cab equipped with efficient heater guarantee comfortable working conditions despite the bad weather.

Different brooms – also with collector box and side brush + water spraying system, and high pressure street cleaners are the ideal tools for cleaning of streets, parks and yards.

The complete AVANT attachment range is available also for various maintenance jobs in parks, gardens, graveyards and other green areas.

Do-it-yourself



Do-it-yourself

AVANT 500 series is an excellent machine for various do-it-yourself jobs – be it smaller earthmoving, material handling, landscaping, sweeping, trenching, lawn mowing... only your imagination sets the limits of what the AVANT can do!

Efficient material handling


For many companies the AVANT 500 series is an ideal allyear-round forklift truck for outdoors material handling.

AVANT has excellent loading and handling capabilities thanks to the telescopic boom and boom self levelling. In addition the AVANT you can also do various property maintenance jobs like sweeping, mowing, snow removal etc.





Technical data, options





Wheels

| Wheel size | Profile | Machine width |
|------------------|------------------|---------------|
| 27 x 8.50 - 15* | tractor | 39.0 in |
| 23 x 8.50 - 12 | tractor or grass | 41.3 in |
| 23 x 10.50 - 12 | tractor or grass | 43.1 in |
| 26 x 12.00 - 12* | tractor or grass | 50.8 in |

^{*)} Bigger wheels will increase total machine height by 1.4 in

| Model | AVANT 520 | AVANT 528 | AVANT 525 LPG |
|--|----------------------|----------------------|----------------------------------|
| Length | 95.7 in | 100.4 in | 95.7 in |
| Width (with 23x10.50-12 wheels) | 43.1 in | 43.1 in | 43.1 in |
| Height | 78.0 in | 78.0 in | 78.0 in |
| Weight | 2315 + 375 lb | 2535 + 375 lb | 2360 + 375 in |
| Standard wheels | 23x10.50-12"grass/TR | 23x10.50-12"grass/TR | 23x10.50-12"grass/TR |
| Transmission, drive | hydrostatic | hydrostatic | hydrostatic |
| Pulling force | 1985 lbf | 2100 lbf | 1985 lbf |
| Drive speed max. | 7.5 MPH | 7.5 MPH | 7.5 MPH |
| Auxiliary hydraulics oil flow / pressure | 8.2 gal/min 185 bar | 9.5 gal/min 200 bar | 9.5 gal/min 185 bar |
| Turning radius inside/outside | 39.2 / 80.7 in | 39.2 / 80.7 in | 39.2 / 80.7 in |
| Max. lifting height (with telescopic boom) | 109.8 in | 109.8 in | 109.8 in |
| Max. lifting capacity (hydr.) | 3000 lb | 3300 lb | 3000 lb |
| Tipping load | 1750 lb | 2100 lb | 1750 lb |
| Max. breakout force / 20 in | 2400 lb | 2800 ІЬ | 2400 lb |
| Engine make and type | Kubota D722 | Kubota D1105 | Kubota DF752 |
| Engine output (ISO Gross) | 20 hp | 28 hp | 23 hp |
| Fuel | Diesel | Diesel | LPG (liquefied petroleum gas) |

Add efficiency and comfort to your work with options.

Boom



Telescopic boom **Cabs**



Self levelling boom



Boom floating



Hydraulic attachment coupling plate



Cab L **Work efficiency**



Cab LX



Cab DLX



FOPS canopy



Joystick



Rear auxiliary hydraulics



Road traffic light kit



Work light kit





Rear side weights, 400 lb (528) Extra weights, trailer coupling



Rear bumper



Hydraulic rear lift (528)



Heavy duty covers



Tilt adapter



Catalytic converter



Heavy duty wheels



Snow chains



Attachment control switch pack



Weather cover



Full weather cover

Drive



Drive release valve



Anti slip valve



Engine block heater



Beacon

Buckets, material handling

General buckets

| Width | Capacity | Weight |
|---------|----------|--------|
| 35 in | 48 gal | 126 lb |
| 41.3 in | 56 gal | 143 lb |
| 43.3 in | 57 gal | 150 lb |
| 50.4 in | 69 gal | 165 lb |
| 55.1 in | 75 gal | 198 lb |

AVANT general buckets are designed to speed up your work and make it more efficient: the operator can see the front edge of the bucket from the driver's seat, which means quick and easy loading and emptying.

There is a grill at the upper end of the bucket which prevents stones from falling towards the operator.

Light material buckets



| Width | Capacity | Weight |
|---------|----------|--------|
| 41.3 in | 106 gal | 210 lb |
| 43.3 in | III gal | 218 lb |
| 50.4 in | I 28 gal | 231 lb |
| 63 in | 161 gal | 275 lb |
| 70.9 in | 181 gal | 302 lb |

AVANT manufactures buckets in different widths and volumes, destined for different types of jobs, e.g. light materials handling (saw dust, manure, wood chips, mulch), snow removal etc.



High tip buckets

| Width | Capacity | Weight |
|---------|----------|--------|
| 41.3 in | 40 gal | 284 lb |
| 50.4 in | 92 gal | 353 lb |
| 70.9 in | 185 gal | 728 lb |

With hight tip bucket you can reach longer and higher than with many bigger machines. The bucket tips over its front edge, which with the telescopic boom means a dump height of 124 in!



4 in I buckets

| Width | Capacity | Weight |
|---------|----------|--------|
| 43.3 in | 40 gal | 335 lb |
| 50.4 in | 45 gal | 386 lb |
| 55.1 in | 50 gal | 419 lb |

Efficient multi purpose bucket - can be used as a normal bucket as well as a dozer blade, leveler, stone picker etc. The front part of the bucket opens with 2 hydraulic cylinders located on the back side of the bucket, which enables dozing, levelling and picking of stones, tree stumps etc. The bucket can also be emptied by opening it, which gives more dumping height. Available with straight edge or with teeth.





| Capacity | 92 gal | 185 gal |
|----------|---------|---------|
| Width | 37.4 in | 54.7 in |
| Weight | 265 lb | 385 lb |

AVANT skip bucket is a very useful attachment for waste collecting and storage as well. Thanks to the two supports you can leave it where you want, fill it and empty it the AVANT way – sitting on the driver's seat. The bucket can also be equipped with a lid.

Grapple bucket



| Width | Weight |
|---------|--------|
| 35.4 in | 287 lb |
| 41.3 in | 320 lb |
| 51.2 in | 364 lb |

Grapple bucket combines a normal bucket and a grapple and is therefore suitable for a multitude of jobs. It can be used for transporting and loading of branches, wood chip, compost, straw, manure etc. It can also be used as a normal bucket with the grapple in the upright position.



Pallet fork

| Length | 33.5 in | 43.3 in |
|--------|---------|---------|
| Weight | 198 lb | 231 lb |

AVANT pallet fork is the right attachment for lifting and handling of different types of light materials on pallets. Fork width is easily adjustable with quick-release locking mechanism. Forks are made of heat treated tapered steel and they comply with the relevant ISO standards.



Log grab

| Log diameter max. | 20 in |
|-------------------|--------|
| Weight | 132 lb |

AVANT log grab mounts on Avant pallet forks. With the log grab you can lift and transport single logs or smaller timber bundles. The grab is equipped with a powerful hydraulic cylinder and it can therefore lift bigger stones and also branches, twigs and similar material.



Jib boom

| > | Boom length | 40.2 in |
|---|-------------|---------|
| | Hooks | 2 pcs |
| | Weight | 66 lb |
| | | |

AVANT jib boom is a simple and ingenious attachment: lifting and moving of heavier loads in tight situations is not a problem when you have this jib boom on your AVANT.

Telescoping jib boom



| Boom length | 40.2 in |
|-------------|---------|
| Hooks | 2 pcs |
| Weight | 66 lb |
| Weight | II0 kg |

Jib boom is an excellent tool for all kinds of lifting tasks which cannot be done with pallet forks. With the jib boom you can lift materials to higher levels and to places that are difficult to reach; with smooth, exact and safe control of the boom. This jib boom with hydraulic telescope is even more efficient and versatile in all lifting jobs.

Digging and construction



Backhoe 210

| Digging depth | 82.7 in |
|----------------|------------------|
| Loading height | 78.7 in |
| Slewing | 140° |
| Buckets | 9.8/15.7/27.6 in |
| Weight | 419 lb |

AVANT backhoe 210 is a very compact and amazingly powerful digging unit. It is very quick and easy to mount on the loader (takes only a couple of minutes), and then you have a unit than can work efficiently even in very tight situations. Low weight allows transportation on trailer. Dozer blade at the bottom of the frame is standard feature.



Backhoe 260

| Digging depth | 102.4 in |
|--------------------|----------|
| Width | 51.2 in |
| Boom slewing angle | 170° |
| Standard bucket | 15.7 in |
| Weight | 925 lb |

Backhoe 260 is a completely new backhoe model from Avant. Boom slewing is executed with two separate cylinders. The new system has less free play when slewing the boom and has less need for servicing. Support legs are hydraulically adjustable. Bucket quick release (manual model) as standard. Mounting the backhoe is now a lot easier with tiltable valve bank and new locking mechanism on the boom.



Digger 150

| Digging depth | 59 in |
|----------------|--------------|
| Loading height | 98 in |
| Buckets | std. 15.7 in |
| Weight | 285 lb |

AVANT Digger 150 is a very efficient and solution for small digging operations where a max. digging depth of 59 in is enough. It is operated with auxiliary hydraulics control lever (or buttons on the joystick), and turning to the side happens by turning the steering wheel. Options: bucket tilt adapter, buckets 10 in, 30 in and 40 in.



Trencher

| Digging depth | max 35 in |
|---------------|-----------|
| Trench width | 4 - 6 in |

With trencher you can easily dig narrow trenches without damaging lawns and gardens – this trencher is ideal for smaller cable or pipe laying. Digging depth is max. 35 in, digging width normally 4 in or 6 in, depending on chain type. Planetary drive with hydraulic motor guarantee efficient and trouble free operation. Three different types of chains available: standard earth chain, frost chain and heavy duty chain with tungsten teeth.



Auger

| | Augers | Max. torque |
|--------------|-------------|-------------|
| Direct drive | 3 - 11.8 in | 1000 lb/ft |
| HD 35 | 3 - 15.7 in | 1390 lb/ft |
| HD 45 | 3 - 23.6 in | 1810 lb/ft |
| HD 58 | 3 - 35.4 in | 2225 lb/ft |

Powerful hydraulic auger with many different auger diameters to suit various tasks, be it post hole boring, tree transplanting etc. Planetary drive gives a lot of torque, replaceable teeth (tungsten teeth as standard) and pilot head enable drilling in hard ground and sandstone also. With the optional extension shafts drilling depth can be increased to max. 98 in.



Hydraulic breaker

| Model | Impact energy | Weight |
|------------|---------------|--------|
| AVANT B70 | 83 ft-lbf | 154 lb |
| AVANT BII0 | 133 ft-lbf | 243 lb |
| AVANT BI60 | 200 ft-lbf | 353 lb |

AVANT breakers are specially designed to give best performance together with AVANT loaders. They are extremely efficient and versatile tools in demolition and refurbishing operations: with the same machine you can do the demolition first and then take the debris away with a bucket – very fast and effective, and you can go almost anywhere with this unit.

Concrete mixing bucket



| | Volume | 71 gal |
|---|-------------|-----------------|
| 3 | Rotation by | hydraulic motor |
| | Weight | 1080 lb |

AVANT concrete mixing bucket is the ideal attachment for situations where electricity is not available or the mixed concrete must be transported and/or lifted to a place not easily accessible. The concrete mixing bucket is powered by a hydraulic motor and emptying happens by tilting the mixer forward.



Winch

| Pulling force | 1000 kp |
|---------------|----------|
| Pulling speed | 7,5 ft/s |
| Cable length | 100 ft |
| Weight | 231 lb |

The AVANT hydraulic winch enables towing of all kinds of objects (e.g. logs, poles, boats) from places where you cannot drive with the machine. The winch is equipped with a safety net, 100 ft of wire rope and a towing hitch. It is powered by a hydraulic motor, mounts on the attachment coupling plate and is operated with the auxiliary hyraulics control lever.



Forklift mast

| Lift height | 69 in |
|---------------|---------------|
| Lift capacity | 3300 lb |
| Fork length | 43.3 in |
| Tyres | 18 x 7.50 - 8 |
| Weight | 660 lb |

The AVANT forklift mast makes your machine a forklift truck. It is an ideal attachment for handling and lifting heavy pallets (stone, fertilizer), big bags and other heavy materials. It can also be used for loading and unloading materials from lorries. The mast is equipped with big foam filled tyres, which gives good all terrain transporting capabilities. Connecting and disconnecting to the loader is fast and easy thanks to the AVANT quick coupling system.



Leguan 50

| Max. allowed load | 440 lb |
|--------------------------------|---------|
| Max. working height | 197 in |
| Height (with lowered platform) | 74.8 in |
| Width | 51.2 in |
| Weight | 893 lb |

The Leguan 50 is mounted directly on to Avants quick attach plate like any other Avant attachment. This makes it fast and easy to mount it on and take it off. The lift is designed according to all access platform directives and it is CE-certified. The safe working load for the lift is 440 lb which means it is allowed for operation with two men or one man with plenty of tools.

Farming



Silage fork

| Width | Weight |
|---------|--------|
| 31.5 in | 185 lb |
| 35.5 in | 220 lb |
| 41.3 in | 265 lb |
| 51.2 in | 310 lb |

YleA robust silage fork equipped with a powerful hydraulic cylinder. The strong blade type pins of the grapple penetrate very well into all types of feed. The fork has replaceable tines, fastened with a bolt, made of reinforced steel.

Dozer blade for silage fork



| Width, main blade | 47.2 in |
|-------------------|---------|
| Width, side blade | 21.7 in |
| Weight | 110 lb |

The dozer blade mounts on the silage fork: just drive the fork into the blade and lock it with the upper grapple of the fork. Destined for cleaning of the floors in cowhouses, stables etc. Equipped with one side blade as standard.

Silage dispenser



| Volume | 172 gal |
|--------|---------|
| Width | 54 in |
| Weight | 530 lb |

This dispenser bucket is equipped with hydraulically driven elevator in the bottom and discharging to both right or left side. Especially recommended for precision chopped silage and feeding stuffs mixed with feeding mixers. Loading from ground is easy by tilting the bucket forward. Distributes silage to about 10 cows / fill - it takes approx. 10 minutes to distribute silage to 50 cows.

Grain / flour dispenser



| Capacity | 80 gal |
|----------|---------|
| Width | 43.3 in |
| Weight | 198 lb |

AVANT grain dispenser is a 80 gal bucket equipped with a hydraulic motor and a \varnothing 8 in screw, destined for distribution of flour, crushed grain etc. Discharges to the right side or to the left side.

The edge of the grain dispenser tilts all the way down so that loading from ground level is very easy.

Straw blower bucket



| Capacity | 175 gal |
|----------|---------|
| Height | 50 in |
| Width | 57.5 in |
| Weight | 265 lb |

With the straw blower bucket you can distribute straw quickly and easily to the cow stalls by driving with your Avant. The blower fan discharges the material up to 10-13 ft distance, depending on engine rpm. The bucket can blow chopped straw, sawdust, turf and small wood chips. The bucket can be equipped, as an option, with a scraper blade which mounts under the bucket, destined for floor cleaning. With the optional side brush one can clean the back part of the stall also. The bucket is available with discharge either to the left or to the right side.

Silage block cutter



Powerful and robust silage cutter with two hydraulic cylinders, can be used with all AVANT loader models. With the silage cutter you can easily cut silage from silo and take it directly to the cattle. Thanks to the open design of the cutting blade visibility during silage distribution is very good. Cuts about 8 animals' silage at one time. Tines are made of reinforced steel

Carousel broom



| Working width | 39.4 in |
|----------------|---------|
| Broom diameter | 39.4 in |
| Broom material | Nylon |
| Weight | 154 lb |

This hydraulically operated broom is a useful attachment when sweeping materials to the side. Rotates in both directions, can be used for various tasks and can be equipped with different types of brooms.

Push Broom



| Width | 51.2 in |
|--------|---------|
| Weight | 75 in |

Push Broom is a handy and inexpensive broom for cleaning smaller areas. Push broom has no rotating parts and the idea is to simply push the material in front of the broom. Push broom can also be used when making pavements. By pushing the filler sand sideways across the paving stones the sand will fall nicely between the stones.

Bale grab



| Weight | 265 lb |
|--------------------|---------|
| Max bale weight | 1985 lb |
| Max. grabber width | 58 in |

With the bale grab you can transport wrapped silage bales, hay bales and other round bales without damaging the bale wrapping. A special grab is available for square bales. Please consult your local Avant dealer.

Square bale grab



| Bale width | 31 - 47 in |
|-------------|--------------|
| Bale weight | max. 2200 lb |
| Weight | 310 lb |

The square bale grab is intended for lifting wrapped square bales. With the grab all liftings are done safely and securely without damaging the plastic wrappings on the bale. Grab hands can be mounted in accordance with the stacking method, to either lift the bales diagonally or lengthwise.

Farming/Landscaping



Round bale spike

| Length | 45.3 in |
|--------|---------|
| Width | 48 in |
| Weight | 120 lb |

With the square bale spike it is easy to lift and transport all square bales without wrappings. Strong and simple construction guarantees a long



Square bale spike

| Length | 45.1 in |
|--------|---------|
| Width | 39.6 in |
| Weight | 130 lb |

With the square bale spike it is easy to lift and transport all square bales without wrappings. Strong and simple construction guarantees a long lifespan.



| | Width | 53 in |
|---|--------|--------|
| è | Weight | 530 lb |

The horse arena harrow is intended for levelling and loosening horse arena riding surfaces. The harrow has two spring loaded tine rows which will loosen the surface, a leveller that will make the surface completely even and a tilling roller that will compact the ground, leaving a great looking finish to the surface. The harrow will not disturb the lower levels (understructure) of the riding surface. Attention: The loader needs to be equipped with single acting rear hydraulics and trailer coupling.

Big bag lifter/transporter



| Lifting hook height | 47.2 in |
|---------------------|---------|
| Width | 39.4 in |
| Weight | 176 lb |

With the big bag lifter/transporter you can lift and transport big bags. This simple attachment makes loading of fertilizer or stacking of big bags as easy as it can get.

Stone collecting bucket



| Width | 41,3 in |
|--------|---------|
| Weight | 210 lb |

The stone collecting bucket is intended mainly for collecting loose stones from the fields after the field has been harrowed. With an Avant it is easy and fast to collect stones from nearby fields.



Wood chipper

| Timber diameter | max. 3.5/6.2 in |
|-----------------|-----------------|
| Chip length | apr. 0.5 in |
| Weight | 660 lb |

With the hydraulic AVANT wood chipper you can quickly chip branches, small tree trunks, logging waste, sawmill residue etc. This powerful double-knife disc chipper is equipped with manual wood feeding. Chips can be directed through 360 degrees by turning the chimney.



Log splitter

| Log diameter | 15.7 in | 15.7 in |
|--------------------|---------|---------|
| Log length | 23.6 in | 39.4 in |
| Splitting capacity | n. 40 k | ogs/min |
| Weight | 330 lb | 550 lb |

AVANT log splitter is equipped with a hydraulic cylinder which pushes the log against the splitting blade. Height of the blade is adjustable, allowing splitting either into two or into four pieces. The splitter has automatic reverse and cylinder stroke can be adjusted with a limit switch. Safety features include a stop switch which prevents operation if the blade cover is not down.



Log cutter/splitter

| 12 in |
|-------|
| 18 in |
| 13" |
| 88 lb |
| |

AVANT log cutter/splitter is a very efficient firewood making machine. It combines a chain saw and a hydraulic log splitter. The log cutter/splitter can be transported with AVANT loader.



Ripper

| Width | 19.7 in |
|---------------|--------------|
| Ripping depth | apr. 11.8 in |
| Weight | 110 lb |

With the powerful AVANT ripper you can break up ground, pull out roots and rip up compacted ground. Equipped with three replaceable tines, ripping angle can be adjusted with the tilt cylinder of the loader.



Leveler

| Width | 47.2 in | 59.1 in |
|--------|---------|---------|
| Weight | 187 lb | 210 lb |

A simple and inexpensive but incredibly useful and efficient attachment for levelling larger areas. With AVANT leveller you can easily and quickly level cultivated soil as a prelude to turfing, seeding or planting, and it can be used effectively in sand schools.

Landscaping

Lawn mower 1200



| Cut width | 47.2 in |
|------------|----------|
| Knives | 2 pcs |
| Cut height | I - 4 in |
| Weight | 375 lb |

AVANT lawn mower is a strong and efficient hydraulic mower deck, equipped with four support wheels. It is a mulching mower, but by removing the mulching blades it can also eject the grass to the side or under the mower. Cutting height can be adjusted independently on each wheel. Thanks to the floating design and big rubber support wheels operation is easy in uneven terrain as well.

Collecting mower



| Cut width | 47.2 in |
|--------------------|----------|
| Knives | 2 pcs |
| Cut height | I - 4 in |
| Collector capacity | 55.5 gal |

With the new AVANT collecting mower you can easily do the mowing and collect the clippings. Thanks to its excellent suction power collecting of leaves from the lawns is also possible.

Flail mower



| Working width | 51.2 in | 59.1 in |
|-------------------|---------|---------|
| Cut height | 1.2 - | 4 in |
| Number of cutters | 36 pcs | 42 pcs |
| Weight | 485 lb | 695 lb |

AVANT flail mower is the right attachment for situations where a normal lawn mower cannot be used and where the cut can be more rough. Cuts efficiently long grass and small scrub and is therefore an ideal tool for road bank mowing and similar jobs. Can be equipped with an extension arm for side mount.

Flail mower with hydraulic boom



| Max. outreach | 138 in |
|---------------|---------|
| Working width | 39.4 in |

With the hydraulic boom flail mower you can easily and efficiently mow ditch banks, road sides, embankments and other slopes that are hard to reach. The flail mower is equipped with proportional joystick controls and is operated from the driver's seat

Finger bar mower

| Width | 55.1 in |
|--------|---------|
| Weight | 155 lb |

AVANT finger bar mower is destined for mowing long hay on fields, meadows and road banks. It is equipped with two moving sickle bars. The long cut hay can be used e.g. for horse feed.

Edge trimmer



| Cutting depth | max. 6 in |
|---------------|-----------|
| Weight | 143 lb |

AVANT edge trimmer is a perfect attachment for trimming the edges of a lawn, hedges, flower arrangements etc. It consists of a hydraulically operated trimmer mounted next to a cutting disc. The trimmer levels the cutting edge. Cut depth is adjustable.

Rotary hoe



| Working width | 51.2 in |
|---------------|-----------|
| Working depth | max. 6 in |
| Weight | 400 lb |

AVANT rotary hoe is designed for heavy use, equipped with hydraulic motor and chain drive. Adjustable cultivating depth up to 6 in - ideal for fine preparation of garden beds, seedbeds, rotovating etc. Can also be equipped with a field roller which makes cultivating depth adjustment easier and levels the cultivated soil.

Stone burier



| Work | ing width | 51.2 in | 59.1 in |
|-------|-----------|---------|---------|
| Work | ing depth | 0 - 5 | .5 in |
| Weigl | nt | 550 lb | 660 lb |
| | nt with | 485 lb | 772 lb |

A professional hydraulic stone burier for preparation of areas to be turfed, seeded or planted. The stone burier cultivates the soil, buries stones and other objects up to 6 in deep in a single pass, leaving a cultivated and consolidated topsoil. Working depth steplessly adjustable with the rear field roller. Separate seeding unit which mounts on the stone burier is also available.

Rotary harrow



| Working width | 48 in | 55.1 in |
|---------------------------|---------|---------|
| Width of the field roller | 53.1 in | 59.1 in |
| Working depth | 0 - 5 | .5 in |
| Weight | 485 lb | 550 lb |

AVANT rotary harrow is an excellent leveler for lawn beds, yards, gardens etc. – for places where the ground needs to be perfectly levelled. It harrows the topsoil only and gives a very nice finish for sowing. Required hydraulics output is lower than that of the stone burier. Working depth is adjusted with the rear field roller which levels the seeding bed during operation.

Stump buster



| Cutting head diameter | I4 in |
|-----------------------|--------|
| Drive shaft length | 20 in |
| Weight | 660 lb |

AVANT stump buster is an efficient, easy and safe way for removing tree stumps. It drills big holes in the stump, gradually removing the stump. The three blade cutting head has slow speed and high torque, which means it can be used within confined spaces and pedestrian areas safely.

Property maintenance



Rotary broom

| Working width | 41.3 in | 51.2 in |
|---------------|---------|---------|
| Broom diam. | 19.7 in | 19.7 in |
| Broom mat. | Ny | lon |
| Weight | 287 lb | 353 lb |

AVANT rotary broom is equipped with a floating bracket (allows about 4 in vertical movement) and three big support wheels in order to follow the contours of the ground. Sweeping angle can be adjusted manually (straight or ±20°) Broom is made of nylon – solid steel or nylon/steel brooms are

Brooms with collector box



| Working width | 41.3 in | 51.2 in |
|-------------------------------|---------|---------|
| Working width with side brush | 53.1 in | 63 in |
| Waste box volume | 45 gal | 53 gal |
| Weight | 507 lb | 838 lb |

AVANT brooms with collector box are specially made for larger yards and street cleaning. Three big support wheels quarantee smooth and easy operation. With the optional side brush cleaning of kerbs and street corners is easy. Collector box emptying is hydraulic - operation with auxiliary hydraulics control lever.

Snow broom



| Working width | 41.3 in | 51.2 in | | |
|---------------|-----------|---------|--|--|
| Broom diam. | 21.7 in | 21.7 in | | |
| Broom mat. | Nylon | | | |
| Angle adjust. | Hydraulic | | | |
| Weight | 287 lb | 353 lb | | |

AVANT snow broom is destined especially for snow sweeping. It has been designed to give the best possible snow cleaning results even on uneven surfaces. This broom can also be used as a normal rotary broom for all year round sweeping.



| Working pressure | 200 bar |
|---------------------|-----------------|
| Water consumption | 1,3 - 8 gal/min |
| Water tank capacity | 71 gal |
| Nozzles | 8 pcs |

This efficient hydraulic washer is fitted with a 71 gal water tank. Max. water pressure is 200 bar, water use is adjustable. Equipped with an adjustable 8 nozzle bar for street washing. A hand held washing gun with 50 ft hose roll is standard equipment as well.

Tipping trailer



| | Load capacity | 2650 lb | 4000 lb |
|--|---------------|------------|----------|
| | Width | 44.3 in | 53.1 in |
| | Length | 67.3 in | 88.2 in |
| | Tyres | 23x8,50-12 | 26×12-12 |
| | Side height | II in | 22 in |

AVANT tipping trailer is available in two models: with carrying capacity of 2650 lb or 4000 lb. Both are equipped with hydraulic tipping. All sides can be removed if necessary. Extra side set is available as an option for the smaller model, on the bigger model it is standard. ATTENTION! The loader must be equipped with the rear auxiliary hydraulics outlet and trailer coupling.

Dozer blade



| Working width | 55 in | 78.7 in |
|---------------|--------|---------|
| Weight | 229 lb | 364 lb |
| Angle | ±30° | ±30° |
| Blade height | 15 in | 19.7 in |

Equipped with hydraulic blade turning, the AVANT dozer blade is the ideal tool for jobs where the materials must be dozed away quickly. Blade is replaceable; standard blade has straight edge, can also be fitted with rubber or saw-type edge for efficient ice cutting.

Snow plow

| 100 | Working width min. and max. | 70.9 in 59.1 in | 86.6 in 70.9 in |
|-----|-----------------------------|--------------------|--------------------|
| | Blade height | 30.3 in | 30.3 in |
| | Plowing angle | ±55° | ±35° |
| | Weight | 617 lb | 672 lb |

AVANT snow plow is the right attachment for efficient snow removal. It consists of two independently adjustable blades. Both blades are spring released and follow very well the contours of the ground thanks to the floating design of the mounting bracket. Angle of each blade can be adjusted separately with electric control switch.

Snow blower 1100

| Working width | 43.3 in |
|------------------|---------|
| Chimney rotation | 270° |

520 lb

Avant snow blower is an efficient attachment for snow removal from sidewalks, foot paths, road and similar places where the snow must be spread out evenly. The two-stage design of the Avant heavy duty snow blower makes it a very efficient snow removal tool - also with wet and heavy snow. First the auger breaks up the snow and moves it into the fan which then throws the snow out through the discharge chute.

Weight

Sand spreader



| Working width | 51.2 in | 59.1 in |
|---------------|------------|------------|
| Capacity | 53 gal | 132 gal |
| Operatio | with hydra | ulic motor |
| Weight | 375 lb | 595 lb |

A hydraulic sand spreader for fast and efficient sand spreading. Front mounting allows loading from ground level in the same way as with normal bucket. Powered by hydraulic motor and equipped with a mixer axle, which prevents the sand from clogging up. The plates in the feeding roll are spring loaded - this means stones will not block or break the spreader.

Centrifugal spreader



| 31-240 in | |
|-----------|--|
| 66 gal | |
| 1100 lb | |
| 287 lb | |
| | |

This robust spreader is destined for spreading of sand, gravel, salt and fertilizers. Spreading width and amount are easy to adjust and spreading can be directed just to one side if necessary.





Avant Tecno USA Inc. 160 Stanley Street Elk Grove Village, IL 60007 847.380.9822 phone 847.380.9823 fax

e-mail: sales@avanttecnousa.com

Familiarise yourself with the wide AVANT loader and attachment range on our website:

www.avanttecnousa.com

On the website you can also download video clips of the machines at work.

AVANT has a policy of continuing improvement, and retains the right to change specifications without notice. © 2012 AVANT Tecno Oy. All rights reserved.